

# Calibration Report for Screen Height Linearity

A Nondestructive testing (NDT) calibration report format suitable for Ultrasonic Equipment calibrations. This is a sample report and may be required to be modified as per specific requirements.

NDT Procedure No: TNE-DOC-UT-02 Rev '0'



## TRINITY NDT®

**An ISO 9001:2008 Certified Company**

Plot No.V-22(A), 6th Main, 2nd Stage, Peenya Industrial Estate, Bangalore-560058, INDIA

Telefax:+91-80-28366466, Mobile:+91 98441 29439, 99009 29439,

E-mail: [info@trinityndt.com](mailto:info@trinityndt.com), Website: [www.trinityndt.com](http://www.trinityndt.com)

This UT calibration report & other NDT reports are available for free download at [www.trinityndt.com](http://www.trinityndt.com)



**TRINITY NDT®**  
An ISO 9001:2008 Certified Company


**SCREEN HEIGHT LINEARITY**

Procedure No. TNE-UT-Doc-02 Rev '0.'

This procedure & other NDT procedures are available for free download at [www.trinityndt.com](http://www.trinityndt.com)

|                  |   |  |                  |
|------------------|---|--|------------------|
| Instrument Model | : |  | SL.No            |
| Manufacturer     | : |  |                  |
| Applicable Code  | : |  | Acceptance Limit |

Sketch:



| Height Of Indication   | 1 <sup>st</sup> Indication | 2 <sup>nd</sup> Indication |
|--|----------------------------|----------------------------|
| Height Of Indication after decrease 10% from start           | 100 %                      |                            |
| Height of Indication after decrease 10% from previous height | 90 %                       |                            |
| Height of Indication after decrease 10% from previous height | 80 %                       |                            |
| Height of Indication after decrease 10% from previous height | 70 %                       |                            |
| Height of Indication after decrease 10% from previous height | 60 %                       |                            |
| Height of Indication after decrease 10% from previous height | 50 %                       |                            |
| Height of Indication after decrease 10% from previous height | 40 %                       |                            |
| Height of Indication after decrease 10% from previous height | 30 %                       |                            |
| Height of Indication after decrease 10% from previous height | 20 %                       |                            |

|       | Tested By | Approved By | Third Party(if required) |
|-------|-----------|-------------|--------------------------|
| Name  |           |             |                          |
| Sign. |           |             |                          |
| Level |           |             |                          |
| Date  |           |             |                          |



**TRINITY NDT®**

An ISO 9001:2008 Certified Company

Aerospace & General NDT | Welding Inspection | Training & Certification | ASNT Level III Consulting | Sales

Visit us: [www.trinityndt.com](http://www.trinityndt.com)